



45°焊接式弯头长型
45° Welded Elbow with straight ends



ISO/IDF No.KST-P004

| Size | D | L1 | R |
|--------|-------|------|-------|
| 1" | 25.4 | 35.0 | 33.5 |
| 1 1/4" | 31.8 | 38.0 | 38.0 |
| 1 1/2" | 38.1 | 45.0 | 48.5 |
| 2" | 50.8 | 50.0 | 60.5 |
| 2 1/2" | 63.5 | 64.0 | 76.2 |
| 3" | 76.2 | 70.0 | 88.5 |
| 4" | 101.6 | 75.0 | 122.0 |


45°卡箍式弯头
45° Clamped Elbow



ISO/IDF No.KST-P005

| Size | B | L1 | R |
|--------|-------|------|-------|
| 1" | 50.5 | 35.4 | 33.5 |
| 1 1/4" | 50.5 | 37.2 | 38.0 |
| 1 1/2" | 50.5 | 41.6 | 48.5 |
| 2" | 64.0 | 46.6 | 60.5 |
| 2 1/2" | 77.5 | 56.1 | 76.2 |
| 3" | 91.0 | 58.2 | 88.5 |
| 3 1/2" | 106.0 | 64.4 | 103.5 |
| 4" | 119.0 | 72.3 | 122.0 |

焊接式四通
Welded Cross



ISO/IDF No.KST-P006

| Size | D | L1 |
|--------|-------|-------|
| 1" | 25.4 | 33.5 |
| 1 1/4" | 31.8 | 38.1 |
| 1 1/2" | 38.1 | 48.5 |
| 2" | 50.8 | 60.5 |
| 2 1/2" | 63.5 | 70.0 |
| 3" | 76.2 | 76.0 |
| 3 1/2" | 89.0 | 86.0 |
| 4" | 101.6 | 100.0 |